

# ANGSTROM SCIENCES, INC.

40 SOUTH LINDEN STREET, DUGUESNE, PA 15110 / PHONE: (412) 469-8466 FAX: (412) 469-8511  
WWW.ANGSTROMSCIENCES.COM

	<b>Cylindrical</b>	<b>Planar</b>
<b><u>Magnets</u></b>		
<b>Target Utilization</b>	<b>85% or Greater</b> (2-4 times the utilization of Planar)	Typical 20-30% High Utilization 40-45%
<b>Vapor Flux</b>	<b>Narrow 10°</b> High Magnet Density Lower Voltage Operation	Wide 30° Lower Magnet Density High Voltage Operation
<b>Contamination</b>	Low <b>Full Center and Outer Erosion</b>	Re-deposition at Center and Corners
<b>Power Consumption</b>	High Magnetic Density enables you to operate at lower power levels, Average <b>Power Savings of 20%</b>	
<b>Throughput</b>	At same power density, <b>20% greater</b>	
<b>Rate</b>	High efficiency cooling allows for <b>higher rate</b>	Target is constantly being heated
<b><u>Material</u></b>		
<b>Amount</b>	<b>3 Times Material</b> as a Planar Target	
<b>Runtime</b>	3 Times the Material <u>+ 2 Times the Utilization</u> <b>= 5 Times the Runtime</b>	
<b>Target Change</b>	NW 50 Flange – <b>10 Minute Change</b>	Multiple bolts – approximately 1 Hour
<b>Cost</b>	Typically Higher	
<b>Availability</b>	Limited - Not All Materials Available	Wider Range
<b>Maintenance</b>	Routine Maintenance every 6 Months	Static – Low Maintenance
<b>Uniformity</b>	<b>Easily Adjustable</b>	Most are Not Adjustable